

variables/V-color

Gripper | Parallel 4 jaws | CHW234





Feature

CHW234

Course	40 mm
Air consumption	16500 mm ³
Function	Double effet
Max cycle per minute	60 cycles
Gripping force*	263.000 N
Weight	2.500 kg
Max. weight of one attachment	0.400 kg
Type	Parallel 4 jaws



Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

4-Jaws Parallel type Cubic Gripper, stroke from 10 to 60mm

*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

These grippers have a integrated dust protection.



Advantages

- Compact-Lightweight-Fast
- Silent mechanism
- Quick and simple integration
- Large opening angle
- Position sensors



Benefits

- No maintenance
- Very short cycle time
- Excellent power/volume ratio
- Low air consumption



expertise in connectivity