


variables/V-color

Micromotors | Coreless BLDC motors | SVTN A 03-2238-12-D-0





Feature

SVTN A 03-2238-12-D-0

Nominal voltage	12 V
No load speed	17445 rpm
No load current	220 mA
Nominal speed	14292 rpm
Nominal torque	6.000 mNm
Nominal current	1.130 A
Stall torque	45.000 mNm
Stall current	7.440 A
Max. efficiency	70.200 %
Torque constant	6.150 mNm/A
Speed constant	1553 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 Pole Brushless DC Motors with Integrated Electronics

SVTN A 03-2238-12-D-0

Speed/torque gradient	407.00 rpm/mNm
Mechanical time constant	6.400 ms
Rotor inertia	1.500 gcm ²

The benefits of this technology join the simplicity of use of a brushed DC motor with the longevity of a brushless motor, maintaining cost-effectiveness and ease of integration. The lack of cogging is typical of the coreless motors and guarantees a reduced ripple torque, a linear correlation between torque, speed, and low inertia. The miniaturization of the electronics allows maintaining the diameter of the motor unvaried with a slight increase in length.



Advantages

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy



Benefits

- Light and compact, easy integration
- High reliability
- Good return on investment
- No need for external drive



p e s

product
engineering
services

expertise in connectivity