

variables/V-color

Magnetic Tool | LAY Series | PLAY50X4 2.0





Feature

PLAY50X4 2.0

Weight	11.30 kg
Max Breakaway ¹	994.30 kg
Working Load ²	248.50 kg
Optimal material thickness	9.50 mm
Max shear	238.00 kg
Magnetic pole footprint	239x71 mm

¹ Safety factor 2:1

² Safety factor 4:1

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Multiple magnets for handling power and control

Ideal for long cylinders, tubing and rough surface finishes, the multiple magnetic fields in LAY units ensure strong holding forces on thin material. Each unit comes with replaceable pole shoes for improved on-site serviceability.



Advantages

- Double effect pneumatic actuator offering high duty cycle
- Custom pole shoes offer mechanical function integration capability
- Linear array of multiple magnets for increased power and increased handling control of long parts with a limited energy consumption
- Intrinsic safety thanks to 183° movement for natural lstop locking



Benefits

- Limited maintenance costs
- Reduced cycle time
- Controlled integration costs



p es

product
engineering
services

expertise in connectivity