

variables/V-color

Encoder | GMI® Angle | GMI-ANG-180





System Data

GMI-ANG-180

Type	Axial, frameless, true absolute Giant Magneto Impedance encoder GMITechnology-FLUX GmbH proprietary
Standard Resolution	24 bits
ENOB in entire mounting tolerance range	22 bits
High Accuracy	$\pm 5.5''$, 0.001° , $\pm 26\mu\text{rad}$
Standard Accuracy	$\pm 7''$, 0.002° , $\pm 35\mu\text{rad}$
Thickness	10.80
Hysteresis	none
Repeatability	1 resolution count
Position update rate and signal latency	Real-time
Power-up Time	max. 0.8 sec



Electrical Data

	OptionAV:min.4.35Vdc.max.36Vdc
Supply voltage	Option5V:min.4.35Vdc.max.6Vdc
	Option24V:min.6Vdc.Max.30Vdc

**Reverse polarity
protection**

yes

Current Consumption

max. 150 mA @ 25 Vdc, max. 140 mA @
24 Vdc



Mechanical Data

Stator Base Material Stainless steel CTE ~ 10 ppm/°C

Stator Weight 520.00 g

Rotor Base Material Stainless steel CTE ~ 10 ppm/°C

Rotor Weight 320.00 g

Vibration EN 60068-2-6, 20 g, 55 .. 2000 Hz

Shock EN 60068-2-27, 200 g, 6 ms



Mounting Tolerances

Nominal Axial (air-gap) 0.30 mm

Axial Tolerance 0.25 mm

Radial Tolerances 0.20 mm



Environmental Data

**Temperature Range - Standard
Operating**

-20°C .. +85°C

Temperature Range - Standard Storage

-20°C .. +85°C

Temperature Range - Extended Operating

-40°C .. +105°C

Temperature Range - Extended Storage

-55°C .. +125°C

Ingress Protection

IP67

EMC Immunity

complies with EN IEC 61000-6-2

EMC Emission

complies with EN IEC 61000-6-4



Advantages



Benefits

- Plug-n-play
- No field calibration required
- Wide mounting tolerances
- High accuracy
- Low installation cost
- Low integration effort
- Easy installation



pes

product
engineering
services

expertise in connectivity